

Australian Standard[®]

**Pressure regulators for use with
industrial compressed gas
cylinders**

This Australian Standard was prepared by Committee ME/2, Gas Cylinders. It was approved on behalf of the Council of Standards Australia on 11 November 1994 and published on 5 February 1995.

The following interests are represented on Committee ME/2:

A.C.T. Occupational Health and Safety Office
Aluminium Development Council
Australian Assembly of Fire Authorities
Australian Chamber of Commerce and Industry
Australian Gas Association
Australian Liquefied Petroleum Gas Association
Australian Underwater Federation
Bureau of Steel Manufacturers of Australia
Department of Defence
Department of Employment, Industrial Relations & Training, Tas.
Department of Employment, Vocational Education, Training & Industrial Relations
Department of Labour, S.A.
Department of Minerals & Energy, Qld
Department of Occupational Health Safety & Welfare, W.A.
Fire Protection Industry Association of Australia
Insurance Council of Australia
Occupational Health & Safety Authority, Vic.
Railways of Australia Committee
Welding Technology Institute of Australia
Work Health Authority
WorkCover Authority of New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 93293.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 4267—1995

Pressure regulators for use with industrial compressed gas cylinders

RECONFIRMATION NOTICE

Technical Committee ME-002 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 21 July 2016.

The following are represented on Technical Committee ME-002:

Australasian Fire and Emergency Service Authorities Council
Australia New Zealand Industrial Gas Association
Australian Chamber of Commerce and Industry
Engineers Australia
Environmental Protection Authority New Zealand
Fire Protection Association Australia
Gas Energy Australia
Gas Technical Regulators Committee
International Accreditation New Zealand
National Association of Testing Authorities Australia
SafeWork NSW
The Australian Gas Association
Welding Technology Institute of Australia
Worksafe New Zealand
WorkSafe Victoria

NOTES

Australian Standard[®]

**Pressure regulators for use with
industrial compressed gas
cylinders**

First published as AS 4267—1995

Incorporating:
Amdt 1 — 1995
Amdt 2 — 1998

PREFACE

This Standard was prepared by the Standards Australia/Standards New Zealand Committee on Gas Cylinders ME/2 to standardise the requirements of pressure regulators for use with industrial compressed gas cylinders.

This Standard is the result of a consensus among representatives on the Joint Committee to produce it as an Australian Standard.

This first edition of the Standard does not cover the range of gaugeless regulators or regulators with pressure indicators. However, these items may be covered in future editions.

Also, this Standard does not incorporate within the regulator design a relief device. This inclusion would rely on industry input once regulators to this Standard have been in the marketplace for a number of years.

Finally, this Standard includes the ‘bomb’ or ‘promoted ignition’ type test as an informative appendix. This may change in a future edition of this Standard to a normative appendix should the demand from industry arise.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the Appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	4
4 GENERAL DESIGN REQUIREMENTS	5
5 SPECIFIC DESIGN REQUIREMENTS	6
6 CONSTRUCTION REQUIREMENTS	6
7 PERFORMANCE	7
8 MARKING	9
APPENDICES	
A PROMOTED IGNITION TEST	10
B OXYGEN SHOCK-TYPE TEST	11
C HYDROSTATIC-TYPE TEST ON HIGH-PRESSURE SIDE OF REGULATOR	13
D GAS PRESSURE RETENTION-TYPE TEST ON LOW-PRESSURE SIDE OF REGULATOR	14
E GAS TIGHTNESS TEST	15
F PERFORMANCE TESTS	16

STANDARDS AUSTRALIA

Australian Standard

**Pressure regulators for use with industrial
compressed gas cylinders**

1 SCOPE This Standard specifies the requirements of pressure regulators for use with industrial compressed gas cylinders.

The mechanisms of pressure regulating valves and regulators for use with medical gas cylinders, together with fixed delivery pressure L.P.G. regulators for domestic and recreational purposes are not covered by this Standard.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

1349 Bourdon tube pressure and vacuum gauges

2473 Valves for compressed gas cylinders (threaded outlet)

2700 Colour standards for general purposes

ISO

2503 Pressure regulators for gas cylinders used in welding, cutting and allied processes

3 DEFINITIONS For the purpose of this Standard, the definitions given in AS 2473 and those below apply.

3.1 Compressed gas regulator—a regulator fitted with inlet fittings complying with AS 2473 and used for reducing a generally variable inlet pressure to an outlet pressure (to be constant as possible) in connection with the flow rate which may be changed.

3.2 Fill pressure—the pressure to which a cylinder is filled with permanent gas, measured when the contents are at an equilibrated temperature of 15°C.

3.3 Flashback arrestor—a device which quenches a flame front (flashback or decomposition).

3.4 Flow rating inlet pressure (p_3)—the inlet pressure at which the maximum flow rating is obtained.

3.5 Maximum outlet pressure (p_2)—the rated maximum outlet pressure the regulator will deliver.

3.6 Maximum working pressure (MWP) of a compressed gas regulator—the maximum pressure at which a regulator is allowed to operate continuously. It is equal to 1.2 times the highest fill pressure of the cylinder to which the regulator is connected.

NOTE: The factor 1.2 takes into account the increase in pressure of the contents of a cylinder when subjected to ambient temperatures higher than the 15°C reference condition. It corresponds approximately to an equilibrated temperature of 50°C of the cylinder contents.

3.7 Nominal inlet pressure (p_1)—the nominal working pressure for which the regulator is designed. It corresponds to the maximum filling pressure, at 15°C, of gas cylinders fitted with the respective valve outlet connection.

3.8 Stabilised outlet pressure (p_4)—the constant outlet pressure of the regulator after flow ceases.