

AS 1319—1994

Reconfirmed 2018

Australian Standard®

---

**Safety signs for the occupational  
environment**

---

This Australian Standard was prepared by Committee SF/5, Industrial Warning Signs. It was approved on behalf of the Council of Standards Australia on 1 February 1994 and published on 18 April 1994.

---

The following interests are represented on Committee SF/5:

Australian Chamber of Commerce and Industry  
Australian and New Zealand Society of Occupational Medicine  
Bureau of Steel Manufacturers of Australia  
Design Institute of Australia  
Electricity Supply Association of Australia  
National Safety Council of Australia  
Occupational Health and Safety Authority, Victoria  
Railways of Australia Committee  
University of N.S.W.  
WorkCover Authority of N.S.W.  
Worksafe Australia

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

---

*This Standard was issued in draft form for comment as DR 93134.*

**STANDARDS AUSTRALIA**

---

**RECONFIRMATION**

**OF**

**AS 1319–1994**

**Safety signs for the occupational environment**

---

**RECONFIRMATION NOTICE**

Major stakeholders of this publication have reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 29 August 2018.

## NOTES

Australian Standard<sup>®</sup>

---

**Safety signs for the occupational  
environment**

---

First published as AS C24—1952.  
Revised and redesignated AS 1319—1972.  
Second edition 1979.  
Third edition 1983.  
Fourth edition 1994.

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 8811 X

## PREFACE

This Standard was prepared by the Standards Australia Committee on Industrial Warning Signs to supersede AS 1319—1983.

The two principal reasons for revising the Standard at this time are firstly to incorporate six new symbolic signs into the Standard, and secondly to alter the basic designs of signs with text messages to incorporate the colour and shape coding of symbolic signs.

The six new signs have been accepted as a result of successful comprehension testing in accordance with procedures similar to those now specified in AS 2342. The testing was carried out by Standards Australia with the financial and practical assistance of a number of large industrial employers in both public and commercial enterprises.

Signs whose function is to warn of hazards and danger have now been grouped under the general heading of hazard signs, and subdivided into DANGER signs and warning signs, the former to be used where the hazard is considered to be potentially life threatening. The term *warning* now replaces the term *caution* in previous editions, for consistency with road signs and water safety signs (neither term is now actually used on signs).

The shape coding for warning signs has been retained as a triangle, despite the use of the diamond as a warning shape for road signs and water safety signs. The Committee considered that the potential for confusion with certain signs in the Hazchem series (see AS 1216\*), notably those for oxidizing agents, would render use of the yellow diamond shape undesirable for general warning signs in the industrial environment.

The text of this Standard has also been modified and expanded to provide more guidance on the design, manufacture and use of industrial safety signs.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

---

\* AS 1216, *Classification, hazard identification and information systems for dangerous goods*.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

	<i>Page</i>
FOREWORD .....	4
 SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE .....	5
1.2 REFERENCED DOCUMENTS .....	5
1.3 DEFINITIONS .....	5
1.4 GENERAL REQUIREMENTS .....	6
 SECTION 2 CLASSIFICATION AND LAYOUT OF SIGNS	
2.1 SIGN CLASSIFICATION AND USE .....	8
2.2 COLOUR, SHAPE AND ENCLOSURE CODING .....	8
2.3 SIGN LAYOUTS .....	8
 SECTION 3 DESIGN OF SIGNS	
3.1 GENERAL REQUIREMENTS .....	15
3.2 USE OF SYMBOLS AND SYMBOLIC SIGNS .....	15
3.3 SIGN LAYOUT DESIGN .....	15
3.4 SIGN SIZE, LEGEND AND LEGIBILITY .....	15
3.5 SIGN FACE MATERIALS AND COLOURS .....	17
 SECTION 4 CONSTRUCTION, INSTALLATION AND MAINTENANCE OF SIGNS	
4.1 SIGN CONSTRUCTION, ERECTION AND REMOVAL .....	19
4.2 SIGN LOCATION .....	19
4.3 SIGN MAINTENANCE .....	20
 SECTION 5 ACCIDENT PREVENTION TAGS	
5.1 GENERAL DESCRIPTION .....	21
5.2 DESIGN OF TAGS .....	21
 APPENDICES	
A SPECIFICATION OF SAFETY COLOURS .....	22
B INDEX OF SYMBOLIC SAFETY SIGNS .....	24
C DESIGN OF DANGER SIGN SYMBOLS .....	33
D GUIDE FOR THE LAYOUT DESIGN OF SAFETY SIGNS .....	34
E GUIDE FOR THE USE OF RETROREFLECTIVE MATERIAL ON SIGNS ..	38
F RECOMMENDED LIGHTING LEVELS FOR ILLUMINATED SIGNS .....	39

## FOREWORD

Symbols and symbolic signs are often regarded as a means of visual communication superior to words. With well designed graphics, a symbolic sign can have greater legibility than one with words, and provided the meaning is reasonably self-evident to the people for whom its message is intended, it can transcend language barriers. However, whether the meaning is sufficiently self-evident cannot be reliably assessed without comprehension testing in accordance with AS 2342. This Standard, therefore, requires that only the symbolic signs specified shall be used, except where a new symbol has been introduced after testing as set out in Clause 3.2.

The Standard also makes provision for combination word/symbol signs. These may be in the form of either a 'composite' sign, where the words are used to qualify or augment the message, or a 'hybrid' sign where the meaning of the symbol is merely repeated in words. Use of the latter is generally deprecated because, if the symbol performed satisfactorily in comprehension testing, it should not be necessary. The need to provide a hybrid sign is generally indicative of a symbol which does not convey its meaning adequately, and therefore, either needs further attention to its design, or should be abandoned in favour of words. However, if a symbol has been accepted entirely on the results of the *recall* test in AS 2342 after having failed the *comprehension* test, its use as a hybrid sign may need to be considered (see Clause 2.3.3(d) of this Standard).



## STANDARDS AUSTRALIA

## Australian Standard

## Safety signs for the occupational environment

## SECTION 1 SCOPE AND GENERAL

**1.1 SCOPE** This Standard sets out requirements for the design and use of safety signs intended for use in the occupational environment to regulate and control safety related behaviour, to warn of hazards and to provide emergency information including fire protection information. It does not include EXIT signs of the type specified in AS 2293.1 for use inside buildings.

**1.2 REFERENCED DOCUMENTS** The following documents are referred to in the Standard:

## AS

1742 Manual of uniform traffic control devices

1742.1 Part 1: General introduction and index of signs

1744 Standard alphabets for road signs

2293 Emergency evacuation lighting in buildings

2293.1 Part 1: Design and installation

2342 Development, testing and implementation of information and safety symbols and symbolic signs

2700 Colour standards for general purposes

## AS/NZS

1906 Retroreflective materials and devices for road traffic control purposes

1906.1 Part 1: Retroreflective materials

## BS

873 Road traffic signs and internally illuminated bollards

873.5 Part 5: Specification for internally illuminated signs and external lighting luminaires

**1.3 DEFINITIONS** For the purpose of this Standard the definitions below apply.

**1.3.1 Background**—that part of a sign that is behind the legend.

**1.3.2 Combination signs**—

- (a) *Combination sign*—a sign which comprises both words and a symbol.
- (b) *Composite sign*—a combination sign on which the words qualify or augment the symbol.
- (c) *Hybrid sign*—a combination sign on which the words simply repeat the message given by the symbol.

**1.3.3 Danger**—applied in the context of safety signs to a situation which is likely to be life threatening if the message is ignored.

**1.3.4 Enclosure**—a coloured band that outlines and emphasizes the symbolic shape of a sign (sometimes referred to as the border).