

Australian Standard[®]

**Battery chargers for lead-acid
batteries—Domestic type**

**Part 1: Battery chargers for
vented cells**

This Australian Standard was prepared by Committee EL/5, Secondary Batteries. It was approved on behalf of the Council of Standards Australia on 9 August 1994 and published on 17 October 1994.

The following interests are represented on Committee EL/5:

Australian Automobile Association
Australian Automotive Aftermarket Association
Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturers Association
Australian Lead Development Association
Department of Defence, Australia
Electricity Supply Association of Australia
Federal Chamber of Automotive Industries, Australia
Institution of Engineers, Australia
Railways of Australia Committee
Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Battery chargers for lead-acid
batteries—Domestic type**

**Part 1: Battery chargers for
vented cells**

First published as AS 2401— 1980. Second edition 1988. Revised and redesignated AS 2401.1 — 1994.
--

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL/5 on Secondary Batteries to supersede AS 2401—1988, *Battery chargers for lead-acid batteries—Household type*.

It is issued as an Australian Standard. The Committee proposes that a Joint Standard be prepared at the next revision.

It applies to domestic battery chargers used for charging lead-acid batteries of the automotive type and vented lead-acid batteries used in semi-traction applications.

The electrical safety requirements for domestic battery chargers are not covered by this Standard but are specified in AS 3100, *Approval and test specification—General requirements for electrical equipment*, and AS 3193, *Approval and test specification—Transformer type battery chargers*.

Consideration has been given to the charging conditions which influence battery service life. The requirements stipulated are intended to ensure optimum battery life. Since the ripple content of the d.c. output of a battery charger is an important factor in battery service life, a ripple requirement has been stipulated.

This Standard contains only minor changes to AS 2401—1988, the most significant of which are—

- (a) the requirement for a maximum percentage ripple current of 85%; and
- (b) the requirement that the maximum temperature of accessible parts shall not exceed the values specified in AS 3100.

This Standard is the first part of a two-part Standard. A proposed second part is to cover battery chargers for sealed cells.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 REFERENCED DOCUMENTS	4
1.3 DEFINITIONS	4
1.4 SAFETY REQUIREMENTS	5
1.5 MARKING	5
1.6 INSTRUCTIONS FOR USE AND CARE	5
SECTION 2 DESIGN AND CONSTRUCTION	
2.1 CORROSION PROTECTION	7
2.2 OUTPUT LEADS	7
2.3 INDICATING DEVICES	7
2.4 CARRYING HANDLE	7
SECTION 3 PERFORMANCE REQUIREMENTS	
3.1 PERCENTAGE RIPPLE CURRENT	8
3.2 RATED CHARGING CURRENT	8
3.3 MAXIMUM VOLTAGE	8
3.4 RADIO/TV INTERFERENCE	8
3.5 MAXIMUM TEMPERATURE OF ACCESSIBLE PARTS	8
SECTION 4 DETERMINATION OF COMPLIANCE ON THE BASIS OF PERFORMANCE	
4.1 PERFORMANCE TESTING	9
APPENDICES	
A DETERMINATION OF RIPPLE CURRENT PERCENTAGE	10
B DETERMINATION OF OUTPUT CHARACTERISTICS	12

STANDARDS AUSTRALIA

Australian Standard**Battery chargers for lead-acid batteries—Domestic type****Part 1: Battery chargers for vented cells**

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE This Standard specifies requirements for battery chargers intended for domestic or similar situations and used for emergency or infrequent charging of vented lead-acid batteries of the automotive type, generally complying with AS 2149.

This Standard does not apply to battery chargers—

- (i) having an input rating greater than 2.5 kVA;
- (i) used for charging sealed cells;
- (iii) used for float charging; and
- (iv) embodied in appliances and not provided with an accessible outlet; and
- (v) for batteries used in cyclic applications.

NOTES:

- 1 AS 4044, specifies requirements for the charging of float-type stationary batteries.
- 2 Battery chargers complying with this Standard are not suitable for charging batteries for an extended time, i.e. they are suitable only for the recharging of batteries.

1.2 REFERENCED DOCUMENTS The documents below are referred to in this Standard:

AS

- 1042 Direct-acting indicating electrical measuring instruments and their accessories
- 1044 Limits and methods of measurement of radio interference characteristics of household electrical appliances, portable tools and similar electrical apparatus
- 1939 Degrees of protection provided by enclosures for electrical equipment (IP Code)
- 2149 Starter batteries—Lead-acid
- 3100 Approval and test specification —General requirements for electrical equipment
- 3193 Approval and test specification —Transformer type battery chargers
- 4044 Battery chargers for stationary batteries

1.3 DEFINITIONS For the purpose of this Standard, the definitions below apply:

1.3.1 Battery charger (charger)—a device which when connected to a low-voltage mains supply provides a d.c. supply source suitable for charging lead-acid batteries.

1.3.2 Nominal charging voltage—the d.c. charging voltage of the charger as given on the nameplate. This may be the nominal voltage of the battery to be charged, e.g. 6, 12, 24 or 48 V.

1.3.3 Rated charging current—the average d.c. charging current of the charger as given on the nameplate.