

AS 3782.4—1990

ISO 7574/4—1985

Australian Standard<sup>®</sup>

---

**Acoustics—Statistical methods  
for determining and verifying  
stated noise emission values of  
machinery and equipment**

**Part 4: Methods for stated values  
for batches of machines**

---

[ISO title: Acoustics—Statistical methods for determining and  
verifying stated noise emission values of machinery and equipment  
Part 4: Methods for stated values for batches of machines]

This Australian Standard was prepared by Committee AV/6, Acoustics, Machinery Noise. It was approved on behalf of the Council of Standards Australia on 26 April 1990 and published on 17 September 1990.

---

The following interests are represented on Committee AV/6:

Australian and New Zealand Environment Council  
Australian Coal Association  
Australian Compressed Air and Mining Equipment Institute  
Australian Federation of Construction Contractors  
Confederation of Australian Industry  
Construction Equipment Importers and Manufacturers of Australia  
Council of the City of Sydney  
Department of Industrial Relations and Employment, N.S.W.  
Department of Labour, S.A.  
Master Builders Construction and Housing Association, Australia  
Metal Trades Industry Association of Australia  
Monash University  
National Association of Australian State Road Authorities  
National Farmers Federation  
Outdoor Power Equipment Association  
Royal Institute of Naval Architects  
Tractor and Machinery Association of Australia  
The University of Melbourne

---

**Review of Australian Standards.** *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

*Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.*

*Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.*

Australian Standard<sup>®</sup>

---

**Acoustics—Statistical methods  
for determining and verifying  
stated noise emission values of  
machinery and equipment**

**Part 4: Methods for stated values  
for batches of machines**

---

First published as AS 3782.4—1990.

## PREFACE

This Standard was prepared by the Standards Australia Committee on Acoustics, Machinery Noise. It is identical with and has been reproduced from ISO 7574/4—1985, *Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment—Part 4: Methods for stating values for batches of machines*.

This Standard is one of the series which deals with statistical methods for determining and verifying noise emission values of machines and equipment, the series being arranged as follows:

*Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment.*

Part 1: *General considerations and definitions*

Part 2: *Methods for stated values for individual machines*

Part 3: *Simple (transition) method for stated values for batches of machines*

Part 4: *Methods for stated values for batches of machines* (this Standard).

For the purpose of this Australian Standard, the ISO text should be modified as follows:

*References:* The references to International Standards should be replaced by references to Australian Standards.

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
4871	Acoustics—Noise labelling of machinery and equipment	3781	Acoustics—Noise labelling of machinery and equipment
7574	Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment	3782	Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment
7574/1	Part 1: General considerations and definitions	3782.1	Part 1: General considerations and definitions

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

	<i>Page</i>
0 INTRODUCTION .....	4
1 SCOPE AND FIELD OF APPLICATION .....	4
2 REFERENCES .....	4
3 DEFINITIONS .....	4
4 GENERAL .....	4
5 GUIDELINES FOR THE DETERMINATION OF THE LABELLED VALUE, $L_c$ , BY THE LABELLER .....	5
6 VERIFYING THE LABELLED VALUE FOR A BATCH OF MACHINES .....	6
7 INFORMATION TO BE GIVEN IN A SPECIFIC LABELLING CODE FOR A SPECIFIC FAMILY OF MACHINES .....	8
ANNEXES	
A OPERATING CHARACTERISTIC CURVES AND EXAMPLES OF SINGLE, DOUBLE AND SEQUENTIAL SAMPLING .....	9
B GUIDELINES FOR ESTIMATING STANDARD DEVIATIONS AND FOR THE USE OF OPERATING CHARACTERISTIC CURVES .....	12
C LIST OF SYMBOLS .....	17
BIBLIOGRAPHY .....	17

# Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment

## Part 4: Methods for stated values for batches of machines

### 0 Introduction

A general introduction to the four-part series of ISO 7574 is given in ISO 7574/1.

For the purposes of this part of ISO 7574, the term “labelled value” stands for all kinds of stated value (e.g. information on a label, the upper noise limit set by an authority, the agreed contract value) for which the methods may be applied.

This part of ISO 7574 contains statistical sampling methods for checking the stated noise emission values for batches (lots) of machines. The labelled value for all machines in a batch is checked by sampling procedures. A reference standard deviation is required when testing the compliance of a batch of a specific family of machines. In addition, information on the type of sampling to be used (single, double or sequential) and the sample size is required. The procedures specified in this part of ISO 7574 assume that the noise emission values of a batch (lot) of machines will follow a normal distribution. The statistical parameters upon which this part of ISO 7574 is based assume that there is a 95 % probability of acceptance if no more than 6,5 % of the noise emission values in a batch exceed the labelled value. Information is included to assist the labeller in determining a labelled value based on these statistical parameters.

The methods given in this part of ISO 7574 ensure that a batch (lot) of machines labelled in accordance with the specifications for the verification procedure have a predetermined probability of acceptance.

### 1 Scope and field of application

This part of ISO 7574 provides guidelines for determining the labelled value,  $L_c$ , by the labeller and specifies statistical sampling procedures for verifying compliance of the noise emissions of a batch (lot) of machinery and equipment with its labelled value.

This part of ISO 7574 is intended to assist those parties responsible for drawing up specific labelling codes for specific families of machines. It is also intended to be

of use to labellers who want their batches of machines to conform with verification procedures that are in accordance with the specifications given in the specific labelling codes based on clause 7.

This part of ISO 7574 does not deal with the consequences that ensue if the stated value is not confirmed as verified for a batch (lot) of machines.

### 2 References

ISO 3951, *Sampling procedures and charts for inspection by variables for percent defective*.

ISO 4871, *Acoustics—Noise labelling of machinery and equipment*.

ISO 7574/1, *Acoustics—Statistical methods for determining and verifying stated noise emission values of machinery and equipment—Part 1: General considerations and definitions*.

### 3 Definitions

For the purposes of this part of ISO 7574, the definitions given in ISO 7574/1 apply.

### 4 General

For a batch of machines, the noise emission values will cover a certain range due to the variability between the machines (relevant measure: standard deviation of production,  $\sigma_p$ ) and due to measurement errors occurring under reproducibility conditions (relevant measure: standard deviation of reproducibility  $\sigma_R$  — see 3.17 in ISO 7574/1). The measure for the overall variability is the total standard deviation  $\sigma_t$ .

The aim of labelling a batch of machines is to indicate as labelled value,  $L_c$ , a limit below which a specified large proportion of the noise emission values of the batch shall lie.  $L_c$  is expressed as an integer in decibels.