Australian Standard®

Open top metal cans—Capacities and related dimensions—Round cans for food and drinks

This Australian Standard was prepared by Committee PK/8. It was approved on behalf of the Council of Standards Australia on 26 October 1989 and published on 7 May 1990.

The following interests are represented on Committee PK/8:

Canmakers Institute of Australia
Confederation of Australian Industry
Department of Primary Industries and Energy
Grocery Manufacturers of Australia
National Standards Commission
Packaging Council of Australia
Standing Committee on Trade Management (Packaging)

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 88190.

Australian Standard®

Open top metal cans—Capacities and related dimensions—Round cans for food and drinks

First published in part as AS 1699 — 1974. AS 2015 first published 1978. AS 1699 — 1974 and AS 2105 — 1978 revised, amalgamated and redesignated AS 2335 — 1980. Second edition 1990.

Incorporating: Amdt 1—1990

PREFACE

This Standard was prepared by Standards Australia Committee on Metal Cans for Food to supersede AS 2355—1980, Hermetically sealed round cylindrical metal cans for food and drinks—Capacities and dimensions.

In this edition the term 'open top can' replaces the former term 'hermetically sealed can', to bring the Standard in line with terminology now generally accepted throughout the world.

The review indicated that several cans previously included in the previous edition are no longer being used, and these have been deleted from this edition. Several additional cans have been included in the range to meet current usage. Consideration was also given to the ISO 3004 series of International Standards, which has recently been revised.

In this edition those sizes of can which conform to the revised ISO specifications are identified. It should be noted that ISO Standard 1361—1983, *Light gauge metal containers—Open top cans—Round cans—Internal diameters*, currently allows the use of 74 mm nominal diameter as an alternative to the 73 mm nominal diameter specified in the ISO 3004 Standards.

Although can height is not specified in ISO Standards, this dimension has been included in this Australian Standard.

CONTENTS

	Pa	O
1	SCOPE	3
2	APPLICATION	3
3	REFERENCED DOCUMENTS	3
4	DEFINITIONS	3
5	CAPACITIES	3
6	DIAMETERS	3
	HEIGHTS	
8	DESIGNATION	3
AP	PENDICES	
A	TOLERANCES FOR NOMINAL GROSS LIDDED CAPACITIES	5
В	NOMINAL DIAMETERS AND TOLERANCES	6

© Copyright - STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS AUSTRALIA

Australian Standard Open top metal cans—Capacities and related dimensions—Round cans for food and drinks

1 SCOPE. This Standard specifies a range of gross lidded capacities with related diameters and heights for round open top metal cans for use in packaging of food and drinks. It applies to three-piece and two-piece cans including cans with necked-in and beaded features.

NOTE: This Standard is intended for use in commercial transactions.

2 APPLICATION. Within Australia, State and Territorial Weights and Measures Authorities require by legislation for some commodities, and recommend for the remainder, that the packing denominations of prepacked articles conform to masses or volumes specified by the Standing Committee on Trade Measurement (Packaging) SCTM (P) (see Note 2).

State and Territorial Authorities, however, have uniformly agreed through the SCTM (P) that for commodities not subject to legislated denominations, cans conforming to this Australian Standard may, for products sold by mass, be used to pack a non-recommended mass, subject to the mass being rounded down to the nearest 5 g or 10 g. If the product is one that is sold by volume, the quantity should be a product volume as listed in column 4 of Table 1 of this Standard.

In certain circumstances the recommended product volumes (in column 4 of Table 1) may not be achieved or the product volumes are not specified. In such cases volumes should be negotiated with the SCTM (P) through a State or Territorial Weights and Measures Authority.

For further information on the SCTM (P) guidelines, reference should be made to any member of the Standing Committee on Packaging.

NOTES:

- 1. Cans for packaging products sold by mass are selected from any specifications in the range. Cans for packaging products sold by volume are selected from those cans for which a product volume is specified.
- 2. Representatives of State and Territorial Authorities and the Commonwealth Attorney-General's Department, with a Chairman and Secretary from the National Standards Commission, meet regularly as a 'Standing Committee on Trade Measurement (Packaging)' to formulate recommendations to maintain uniformity of intent in the State and Territorial Weights and Measures Deceptive Practices in Packaging, and Commonwealth Import Legislation controlling packaged goods
- 3 REFERENCED DOCUMENTS. The document below is referred to in this Standard.
- AS 2354 Open top metal cans—Definitions and determination methods for dimensions and capacities
- **4 DEFINITIONS.** For the purpose of this Standard the definitions given in AS 2354 apply.
- **5 CAPACITIES.** Nominal gross lidded capacities, i.e. the total internal capacities of the closed can, shall be as given in Table 1. Tolerances for gross lidded capacities shall be in accordance with Appendix A.

NOTE: For information only, the Note to Table 1 provides a method of calculating, from the internal diameter and height, the approximate gross lidded capacity.

6 DIAMETERS. Nominal diameters for each gross lidded capacity are given in Table 1. Internal diameters shall be as specified in Appendix B.

NOTE: Measurement of the distance between diametrically opposite points on the inside of the double seam is a method of determining the approximate internal diameter.

Where necked-in cans are specified, the nominal necked-in diameters shall be as specified in Table 1. The opening diameter, namely the internal diameter of the can extremity to which the end is fixed, shall conform to the requirements specified in Table B1 of Appendix B.

- **7 HEIGHTS.** Nominal heights for each gross lidded capacity shall be as specified in Table 1. The height, namely the distance from the lowest point of the can to the top edge of the upper double seam, shall not vary by more than ± 1.0 mm from the nominal height for cans of gross lidded capacity below 750 mL, or ± 2 mm for cans of gross lidded capacity 750 mL or greater.
- **8 DESIGNATION.** Cans shall be designated by nominal gross lidded capacity, and nominal diameter and nominal height expressed in millimetres.