

AS 3610 Supplement 1—1995

**Formwork for concrete—Blowhole
and colour evaluation charts
(Supplement to AS 3610—1995)**

This Australian Standard was prepared by Committee BD/43, Formwork. It was approved on behalf of the Council of Standards Australia on 20 October 1989 and published on 9 April 1990.

The following interests are represented on Committee BD/43:

Aluminium Development Council
Association of Consulting Engineers, Australia.
Australian Federation of Construction Contractors
Australian Precast Concrete Manufacturers Association
Austroads
Cement and Concrete Association of Australia
CSIRO, Division of Building, Construction and Engineering
Department of Employment, Vocational Education, Training and Industrial Relations, Qld.
Department of Occupational Health Safety and Welfare, W.A.
Formwork Contractors of Western Australia
Master Builders Construction and Housing Association Australia
Metal Trades Industry Association of Australia
Plywood Association of Australia Ltd
Precast Concrete Manufacturers Association of New South Wales
Public Works Department New South Wales
Queensland University of Technology
Workcover Authority New South Wales

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 86123.

Australian Standard[®]

**Formwork for concrete—Blowhole
and colour evaluation charts
(Supplement to AS 3610—1995)**

First published as AS 3610 Supplement 1—1990.

Incorporating:
Amdt 1 — 1995

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5997 7

PREFACE

This Supplement was prepared by the Standards Australia Committee on Formwork.

The Supplement is identical in technical content to Appendix B in AS 3610—Formwork for concrete, but differs in that additional copies of the photographic charts for surface finish and colour control are provided.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

APPENDIX B
BLOWHOLE AND COLOUR EVALUATION CHARTS

(This Appendix forms an integral part of this Standard.)

B1 BLOWHOLE EVALUATION CHART. The photographs in Figures B1 to B3 shall be used in accordance in Clauses 3.4, 3.6 and 5.6 Photographs are in pairs consisting of—

- (a) a general photograph at scale 1:5 which gives a clear idea of expected variation in blowhole size and distribution; and
- (b) a close up photograph at scale 1:1 showing an area which is representative of the general photograph.

The photographs, in conjunction, set limits of acceptability in each of Classes 1, 2 and 3.

NOTE: It is possible that there will be small sections of the 1:5 scale photograph which exhibit a greater concentration of blowholes, or ones of larger size than are shown in the 1:1 scale photograph. This is consistent with the intention of Table 3.4.2.

B2 COLOUR EVALUATION CHART. The Chart in Figure B4 is suitable for use with most grey concretes as set out in Clauses 3.5, 3.6 and 5.6. Similar charts, or other suitable means, should be developed for use with other colours of concrete.