

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 2.1: General—Guidelines for
the selection of methods**

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 9 April 1990 and published on 10 December 1990.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Australian Water and Wastewater Association
Board of Works, Melbourne
Department of Water Resources, NSW
Engineering and Water Supply Department of South Australia
Forestry Commission, NSW
Institute of Instrumentation and Control
Monash University
Public Works Department, NSW
Showy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney
Water Resources Commission, Queensland

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 2.1: General—Guidelines for
the selection of methods**

First published as AS 3778.2.1—1990.

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 8363—1986, *Liquid flow measurement in open channels—General guidelines for the selection of methods*.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: Vocabulary and symbols
- Part 2.1: General—Guidelines for the selection of methods of measurement (this Standard)
- Part 2.2: General—Establishment and operation of a gauging station
- Part 2.3: General—Determination of the stage-discharge relation
- Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
- Part 2.5: General—Guidelines for the selection of flow gauging structures
- Part 3: Velocity-area methods—
 - Method 3.1: Measurement by current-meters and floats
 - Method 3.2: Measurement by moving-boat method
 - Method 3.3: Measurement by slope-area method
 - Method 3.4: Collection and processing of data for determination of errors in measurement
 - Method 3.5: Investigation of total error
 - Method 3.6: Measurement of flow in tidal channels
 - Method 3.7: Measurement by ultrasonic (acoustic) method
 - Method 3.8: Electromagnetic method using a full-channel-width coil
- Part 4: Measurement using flow gauging structures—
 - Method 4.1: Thin-plate weirs
 - Method 4.2: Rectangular broad-crested weirs
 - Method 4.3: Round-nose horizontal broad-crested weirs
 - Method 4.4: V-shaped broad-crested weirs
 - Method 4.5: Triangular profile weirs
 - Method 4.6: Flat-V weirs
 - Method 4.7: Rectangular, trapezoidal and U-shaped flumes
 - Method 4.8: Trapezoidal profile weirs
 - Method 4.9: Parshall and Saniiri flumes
 - Method 4.10: End-depth method for estimation of flow in rectangular channels with a free overfall
 - Method 4.11: End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)
- Part 5: Dilution methods—
 - Method 5.1: Constant-rate injection method for the measurement of steady flow
 - Method 5.2: Integration method for the measurement of steady flow
- Part 6.1: Measuring devices, instruments and equipment—Rotating element current-meters
- Part 6.2: Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment
- Part 6.3: Measuring devices, instruments and equipment—Calibration of rotating element current—meters in straight open tanks
- Part 6.4: Measuring devices, instruments and equipment—Echo sounders for water depth measurements
- Part 6.5: Measuring devices, instruments and equipment—Water level measuring devices
- Part 6.6: Measuring devices, instruments and equipment—Cableway system for stream gauging
- Part 6.7: Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters
- Part 6.8: Measuring devices, instruments and equipment—Position fixing equipment for hydrometric boats

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Wherever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (b) Wherever the word 'fluid' appears, it should be read as 'water'.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement of water flow in open channels

Part 2.1: General—Guidelines for the selection of methods

1 Scope and field of application

This International Standard gives general guidelines for the selection of a suitable method for liquid flow measurements in open channels. More specific guidelines are contained in International Standards relevant to each method.

2 Methods of measurement

Methods which are suitable for liquid flow measurements in open channels and which form the subjects of International Standards¹⁾ are as follows

- 1) Velocity-area method by wading.
- 2) Velocity-area method from a bridge.
- 3) Velocity-area method using a cableway.
- 4) Velocity-area method using a static boat.
- 5) Velocity-area method using a moving boat.
- 6) Velocity-area method using floats.
- 7) Slope-area method.
- 8) Ultrasonic method.
- 9) Electromagnetic method.
- 10) Dilution method with a chemical tracer (continuous injection).
- 11) Dilution method with a chemical tracer (sudden injection).
- 12) Dilution method with a radioactive tracer (sudden injection).
- 13) Dilution method with a radioactive tracer (continuous injection).
- 14) Cubature method.

- 15) Thin-plate weirs (sharp crest, V-notch).
- 16) Thin-plate weirs (sharp crest, rectangular, with suppressed side contractions).
- 17) Thin-plate weirs (sharp crest, rectangular, with side contractions).
- 18) Weirs (broad-crested with sharp upstream edge).
- 19) Weirs (broad crested with rounded upstream edge).
- 20) Weirs (triangular profile).
- 21) Weirs (triangular profile, flat-V).
- 22) Weirs (V-shaped, broad-crested).
- 23) Flumes (rectangular throated).
- 24) Flumes (trapezoidal throated).
- 25) Flumes (U-shaped throat).
- 26) Free overfalls, end-depth method (rectangular and non-rectangular channels).

3 Principles of measurement

3.1 Velocity-area methods

3.1.1 Methods using current-meters

The velocity and cross-sectional area of flow in an open channel are measured. The discharge is determined from the product of this velocity and area.

The velocity may be measured by a current-meter. When measurements using current-meters are not feasible, the velocity is measured by floats.

3.1.2 Moving boat method

The moving boat method employs a modification of the conventional current-meter measurements in the velocity-

1) See the bibliography for a list of these International Standards.