

Australian Standard[®]

**Measurement of water flow in
open channels**

Part 1: Vocabulary and symbols

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 18 May 1990 and published on 10 December 1990.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Australian Water and Wastewater Association
Board of Works, Melbourne
Department of Water Resources, NSW
Engineering and Water Supply Department of South Australia
Forestry Commission, NSW
Institute of Instrumentation and Control
Monash University
Public Works Department, NSW
Snowy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney
Water Resources Commission, Queensland

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Measurement of water flow in
open channels**

Part 1: Vocabulary and symbols

First published as AS 3778.1—1990.

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 772—1988, *Liquid flow measurement in open channels—Vocabulary and symbols*.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: Vocabulary and symbols (this Standard)
- Part 2.1: General—Guidelines for the selection of methods of measurement
- Part 2.2: General—Establishment and operation of a gauging station
- Part 2.3: General—Determination of the stage-discharge relation
- Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
- Part 2.5: General—Guidelines for the selection of flow gauging structures
- Part 3: Velocity-area methods—
 - Method 3.1: Measurement by current-meters and floats
 - Method 3.2: Measurement by moving-boat method
 - Method 3.3: Measurement by slope-area method
 - Method 3.4: Collection and processing of data for determination of errors in measurement
 - Method 3.5: Investigation of total error
 - Method 3.6: Measurement of flow in tidal channels
 - Method 3.7: Measurement by ultrasonic (acoustic) method
 - Method 3.8: Electromagnetic method using a full-channel-width coil
- Part 4: Measurement using flow gauging structures—
 - Method 4.1: Thin-plate weirs
 - Method 4.2: Rectangular broad-crested weirs
 - Method 4.3: Round-nose horizontal broad-crested weirs
 - Method 4A: V-shaped broad-crested weirs
 - Method 4.5: Triangular profile weirs
 - Method 4.6: Flat-V weirs
 - Method 4.7: Rectangular; trapezoidal and U-shaped flumes
 - Method 4.8: Trapezoidal profile weirs
 - Method 4.9: Parshall and Saniiri flumes
 - Method 4.10: End-depth method for estimation of flow in rectangular channels with a free overfall
 - Method 4.11: End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)
- Part 5: Dilution methods—
 - Method 5.1: Constant-rate injection method for the measurement of steady flow
 - Method 5.2: Integration method for the measurement of steady flow
- Part 6.1: Measuring devices, instruments and equipment—Rotating element current-meters
- Part 6.2: Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment
- Part 6.3: Measuring devices, instruments and equipment—Calibration of rotating element current-meters in straight open tanks
- Part 6.4: Measuring devices, instruments and equipment—Echo sounders for water depth measurements
- Part 6.5: Measuring devices, instruments and equipment—Water level measuring devices
- Part 6.6: Measuring devices, instruments and equipment—Cableway system for stream gauging
- Part 6.7: Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters
- Part 6.8: Measuring devices, instruments and equipment—Position fixing equipment for hydrometric boats

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Wherever the words 'International Standard' appear; referring to this Standard, they should be read as 'Australian Standard'.
- (b) Wherever the word 'fluid' appears, it should be read as 'water'.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement of water flow in open channels— Vocabulary and symbols

0 Introduction

When preparing this International Standard, the following three principles were adopted wherever possible:

- a) to standardize suitable terms and symbols without perpetuating unsuitable ones;
- b) to discard any term or symbol which has been used with differing meanings in different countries, or by different people, or by the same person at different times, and to replace that term or symbol by one which has an unequivocal meaning;
- c) to exclude terms which are self-evident.

However, it is recognized that it is not possible to produce a complete set of definitions which will be universally acceptable, but it is hoped that the definitions provided and the symbols used will find widespread acceptance and that their use will lead to better understanding among practitioners of the measurement of liquid flow in open channels.

Throughout this International Standard there are instances of synonymous terms and of preferred terms or alternative spellings. Translations of terms which have no exact equivalent are given in parentheses.