

AS 1597.2 Supplement 1—1997

---

**Precast reinforced concrete box  
culverts**

**Part 2: Large culverts (from  
1500 mm span and up to and  
including 4200 mm span and  
4200 mm height)—Commentary**

**(Supplement to AS 1597.2—1996)**

---

This Australian Standard was prepared by Committee CE/26, Precast Reinforced Concrete Box Culverts. It was approved on behalf of the Council of Standards Australia on 24 January 1997 and published on 5 March 1997.

---

The following interests are represented on Committee CE/26:

Association of Consulting Engineers, Australia  
Australasian Railway Association  
Australian Chamber of Commerce and Industry  
Australian Geomechanics Society  
AUSTROADS  
Cement and Concrete Association of Australia  
Concrete Pipe Association of Australasia  
Institute of Municipal Engineering, Australia  
Institution of Engineers, Australia  
National Precast Concrete Association  
Swinburne Institute of Technology  
University of Adelaide  
University of Sydney

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS 1597.2 Supplement 1—1997

---

**Precast reinforced concrete box  
culverts**

**Part 2: Large culverts (from  
1500 mm span and up to and  
including 4200 mm span and  
4200 mm height)—Commentary**

**(Supplement to AS 1597.2—1996)**

---

First published as AS 1597.2 Supplement 1—1997.

## PREFACE

This Commentary was prepared by the Standards Australia Committee CE/26, Precast Reinforced Concrete Box Culverts. It is intended that it be read in conjunction with AS 1597.2—1996, *Precast reinforced concrete box culverts, Part 2: Large culverts (from 1500 mm span and up to and including 4200 mm span and 4200 mm height)*, but does not form part of that Standard.

In preparing AS 1597.2, the Committee considered it desirable that only necessary requirements be detailed in the new Standard and that any additional explanations, advice or comments be brought to the attention of the designer and other users of the Standard by this Commentary.

The purpose of this Commentary is as follows:

- (a) To provide background reference material to the clauses of the Standard.
- (b) To indicate the origin of particular requirements.
- (c) To indicate departures from existing codes or Standards for concrete structure design practice.
- (d) To explain the application of certain clauses.

For ease of cross-reference, section numbers, paragraph numbers and titles used in the Commentary are the same as those used in the body of the Standard but are prefixed with the letter C. Figures, however, are designated C1, C2 and the like and do not correspond to those in the Standard.

References noted in the Commentary text are listed at the end of the Commentary.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

	<i>Page</i>
<b>SECTION C1 SCOPE AND GENERAL</b>	
C1.1 SCOPE . . . . .	5
C1.2 APPLICATION . . . . .	5
C1.3 REFERENCED DOCUMENTS . . . . .	5
C1.4 DEFINITION . . . . .	5
C1.5 NOTATION . . . . .	6
C1.6 USE OF ALTERNATIVE MATERIALS OR METHODS . . . . .	6
C1.7 TYPES OF CULVERTS . . . . .	6
C1.8 CLASSIFICATION . . . . .	6
<b>SECTION C2 MATERIALS, MANUFACTURE AND DIMENSIONING</b>	
C2.1 SCOPE . . . . .	7
C2.2 FORMWORK . . . . .	7
C2.3 REINFORCEMENT . . . . .	7
C2.4 CONCRETE MATERIALS . . . . .	7
C2.5 SPECIFICATION AND MANUFACTURE OF CONCRETE . . . . .	7
C2.6 HANDLING, PLACING AND FINISHING OF CONCRETE . . . . .	7
C2.7 CURING . . . . .	8
C2.8 JOINTS . . . . .	8
C2.9 DIMENSIONS . . . . .	8
C2.10 COVER TO REINFORCEMENT . . . . .	8
C2.11 MEASUREMENT OF DIMENSIONS . . . . .	9
C2.12 TOLERANCES . . . . .	9
C2.13 PROVISION FOR LIFTING . . . . .	9
C2.14 WORKMANSHIP AND FINISH . . . . .	9
C2.15 DEFECTS . . . . .	9
C2.16 MARKING . . . . .	9
C2.17 FINISHING AND REPAIRS . . . . .	9
<b>SECTION C3 DESIGN REQUIREMENTS AND PROCEDURES</b>	
C3.1 GENERAL . . . . .	10
C3.2 DESIGN LOADS . . . . .	10
C3.3 LOAD EFFECT ANALYSIS . . . . .	17
C3.4 THEORETICAL STRENGTH AND SERVICEABILITY CALCULATIONS . . . . .	17
C3.5 REINFORCEMENT DETAILING . . . . .	18
C3.6 EXAMPLE OF THE DESIGN OF AN INVERTED U-SHAPED CULVERT TO AS 1597.2 . . . . .	18
<b>SECTION C4 LOAD TESTING FOR DESIGN</b>	
C4.2 GENERAL REQUIREMENTS . . . . .	26
C4.3 TEST SPECIMENS . . . . .	26
C4.4 TEST LOADS . . . . .	26
C4.6 PROTOTYPE PROOF-LOAD TESTS FOR ULTIMATE STRENGTH . . . . .	26
C4.7 PROTOTYPE FAILURE LOAD TESTS . . . . .	27

SECTION C5 ROUTINE SAMPLING AND TESTING

C5.1	GENERAL . . . . .	28
C5.2	REQUIRED TESTS . . . . .	28
C5.3	SAMPLING FOR LOAD TESTING . . . . .	28
C5.4	COMPLIANCE . . . . .	28
C5.5	ACCEPTANCE . . . . .	28

SECTION C6 INSTALLATION

C6.1	SCOPE . . . . .	29
C6.2	EXCAVATION . . . . .	29
C6.3	FOUNDATION PREPARATION . . . . .	29
C6.4	PLACING PRECAST UNITS . . . . .	29
C6.5	COMPACTION . . . . .	30
C6.6	BACKFILLING . . . . .	30

APPENDICES

CG	FLOW CHARTS FOR PROTOTYPE TESTING . . . . .	31
CJ	TABLES OF BASIC TEST LOADS FOR STANDARD CULVERT UNITS AND LINK SLABS . . . . .	34

## STANDARDS AUSTRALIA

### Australian Standard

### Precast reinforced concrete box culverts

#### Part 2: Large culverts

(from 1500 mm span and up to and including 4200 mm span and 4200 mm height)—Commentary (Supplement to AS 1597.2—1996)

## SECTION C1 SCOPE AND GENERAL

**C1.1 SCOPE** Although the primary use of the box culverts is for carrying water, the application of this Standard's requirements to box culverts used for other purposes such as pedestrian or vehicular underpasses, escape or reclaim tunnels or earth-retaining structures is considered to be acceptable.

The limit on culvert dimensions of length, height and span are set only to give acceptable boundaries for the work of the Committee. The design of culvert units with larger dimensions may be carried out using the principles given in Section 3 or Section 4 provided that the designer has adequately addressed the effects of increased dimension on load and structural responses. Particular care should be exercised in the adoption of equivalent loadings which may not be suitable for culverts larger than 4200 mm span and 4200 mm leg height.

Each special culvert should be individually designed for its unique condition. Where large holes are required in a unit, the remaining cross-section should be designed to resist the total bending moment and shear applied to the culvert. A similar approach should be adopted for a skewed unit in combination with the relevant provisions of this Standard.

The maximum height of fill is limited to 10 m since the effect of soil arching in deep fills has not been considered when determining loads on the culvert. This simplification will result in a conservative result in high fill situations, however the degree of conservatism was considered acceptable by the Committee for fills up to 10 m.

**C1.2 APPLICATION** No comment.

**C1.3 REFERENCED DOCUMENTS** The Standards listed are subject to revision from time to time. A check should be made with Standards Australia as to the currency of any Standard referenced in the text.

#### **C1.4 DEFINITION**

**C1.4.1 Administrative** No comment.

#### **C1.4.2 Technical**

**C1.4.2.12 Fill** The term 'fill' is used throughout with a qualifier indicating particular requirements as follows:

- (a) *Backfill or embankment fill* The Standard deals with the backfill and embankment fill from the aspect of culvert performance only. In installations involving road and railway embankments, or trenches through urban areas, the stability criteria for the finished surface above the culverts may impose more restrictive requirements on the fill specification.