

Australian Standard[®]

**Rotating electrical machines—
General requirements**

**Part 30: Preferred outputs and
frame sizes**

This Australian Standard was prepared by Committee EL/9, Rotating Electrical Machinery. It was approved on behalf of the Council of Standards Australia on 21 February 1997 and published on 5 July 1997.

The following interests are represented on Committee EL/9:

Australian British Chamber of Commerce
Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturers Association
Bureau of Steel Manufacturers of Australia
Department of Defence
Electricity Supply Association of Australia
Institution of Engineers Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 96207.

Australian Standard[®]

**Rotating electrical machines—
General requirements**

**Part 30: Preferred outputs and
frame sizes**

Originated in part as part of AS C34—1927.
Previous edition AS 1359.30—1987.
Revised and designated in part as AS 1359.30—1997.

PREFACE

This Standard was prepared by the Standards Australia Committee EL/9, Rotating Electrical Machinery, to supersede, in part, AS 1359.30—1987, *Rotating electrical machines—General requirements*, Part 30: *Duty and rating*.

The remainder of AS 1359.30—1987 has been superseded by AS 1359.101 —1997, Part titled, *Rating and performance*.

This Standard is a Part of the AS 1359 series listed in AS 1359.0, Part titled, *Introduction and list of Parts*.

The objective of this Standard is to provide the rotating electrical machine industry with preferred machine outputs, and preferred allocations of outputs to standard frame sizes for certain three-phase induction motors.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 APPLICATION	4
3 REFERENCED DOCUMENTS	4
4 PREFERRED OUTPUT RATINGS	4
5 PREFERRED ALLOCATIONS OF OUTPUT TO FRAME SIZE	4
 TABLES	
1 GENERATORS—PREFERRED OUTPUTS	5
2 MOTORS—PREFERRED OUTPUTS	6
3 THREE-PHASE CAGE-ROTOR INDUCTION MOTORS— S1 DUTY RATING, UP TO 690 V, 50 HZ— COOLING: IC 01, ENCLOSURE: IP 22 (ENCLOSED-VENTILATED)— PREFERRED ALLOCATION OF OUTPUT TO FRAME SIZE	7
4 THREE-PHASE WOUND-ROTOR INDUCTION MOTORS— S1 DUTY RATING, UP TO 690 V, 50 HZ— COOLING: IC 01, ENCLOSURE: IP 22 (ENCLOSED-VENTILATED)— PREFERRED ALLOCATION OF OUTPUT TO FRAME SIZE	8
5 THREE-PHASE CAGE-ROTOR INDUCTION MOTORS— S1 DUTY RATING, UP TO 690 V, 50 HZ— COOLING: IC 411, ENCLOSURE: IP 44 (TOTALLY-ENCLOSED FAN-COOLED)— PREFERRED ALLOCATION OF OUTPUT TO FRAME SIZE	9
6 THREE-PHASE WOUND-ROTOR INDUCTION MOTORS— S1 DUTY RATING, UP TO 690 V, 50 HZ— COOLING: IC 411, ENCLOSURE: IP 44 (TOTALLY-ENCLOSED FAN-COOLED)— PREFERRED ALLOCATION OF OUTPUT TO FRAME SIZE	10
7 THREE-PHASE CAGE-ROTOR INDUCTION MOTORS— S1 DUTY RATING, UP TO 690 V, 50 HZ— COOLING: IC 418, ENCLOSURE: IP 44 (FRAME-SURFACE-AIRSTREAM COOLED)— PREFERRED ALLOCATION OF OUTPUT TO FRAME SIZE AND ASSOCIATED AIRSTREAM VELOCITIES	11

STANDARDS AUSTRALIA

Australian Standard

Rotating electrical machines—General requirements

Part 30: Preferred outputs and frame sizes

1 SCOPE This Standard specifies preferred rated outputs for machines, and preferred allocations of outputs to standard frame sizes for certain three-phase induction motors.

2 APPLICATION This Standard is intended to be read in conjunction with AS 1359.2, AS 1359.10, AS 1359.20, AS 1359.101, and AS 1359.106.

3 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

1359	Rotating electrical machines—General requirements
1359.2	Part 2: Dimensional symbols
1359.10	Part 10: Designations and dimensions
1359.20	Part 20: Classification of types of enclosure
1359.101	Part 101: Rating and performance
1359.106	Part 106: Methods of cooling (IC Code)
1939	Degrees of protection provided by enclosures for electrical equipment (IP Code)

CENELEC

HD 231 S1 Dimensions of three-phase induction motors

4 PREFERRED OUTPUT RATINGS Preferred output ratings are as follows:

- (a) For generators Table 1.
- (b) For motors Table 2.

5 PREFERRED ALLOCATIONS OF OUTPUT TO FRAME SIZE

NOTE: The terms ‘enclosed-ventilated’, ‘totally enclosed fan-cooled’, and ‘frame-surface-airstream-cooled’ are imprecise and are used herein because of widespread use in the industry. Where there is any possibility of confusion, the more precise IC Code and IP Code should be used. The IC Code is specified in AS 1359.106. The IP Code is specified in AS 1359.20 which refers, in the main, to AS 1939.

5.1 Three-phase ‘enclosed-ventilated’ induction motors Preferred outputs relative to frame size of three-phase ‘enclosed-ventilated’ induction motors, with duty rating S1 and voltage rating up to 690 V, 50 Hz, are specified as follows:

- (a) For cage-rotor motors Table 3.
- (b) For wound-rotor motors Table 4.

NOTE: Two sets of allocations are specified from different sources—see footnotes to the tables.